


Towards Unsupervised Sketch-based Image Retrieval

Conghui Hu¹ Yongxin Yang² Yunpeng Li³ Timothy M. Hospedales² Yi-Zhe Song³

¹ National University of Singapore ² University of Edinburgh ³ University of Surrey



Unsupervised Sketch-based Image Retrieval:




Problem definition:

retrieve photos of the same category as input sketch with


- no category annotations
- no sketch-photo pairing

Proposed solution

- compute a soft correspondence between sketch and photo domains
- learn a representation that aligns sketch and photo features under the soft correspondence, and is also semantically meaningful.



Our framework:



Results:


Retrieval accuracy on Sketchy-Extended:

| Method | Sketchy-Extended dataset | | |
|--------------------------|--------------------------|--------------|--------------|
| | Prec@200(%) | mAP@200 (%) | mAP (%) |
| RotNet [17] | 2.26 | 4.89 | 1.54 |
| ID [38] | 3.41 | 5.26 | 2.45 |
| CDS [20] | 2.37 | 3.58 | 1.88 |
| GAN [18] | 2.45 | 4.66 | 1.43 |
| SwAV [5] | 10.87 | 12.51 | 10.15 |
| DSM [29] | 10.07 | 17.92 | 4.28 |
| SwAV [5] + CycleGAN [45] | 4.15 | 5.39 | 4.28 |
| SwAV [5] + GAN [18] | 22.96 | 25.48 | 18.82 |
| Ours | 33.64 | 36.31 | 28.17 |

Ablation study:

| Method | JDOT | Proto. | Mem. bank | Sketchy-Extended dataset | | |
|--------|------|--------|-----------|--------------------------|--------------|--------------|
| | | | | Prec@200(%) | mAP@200 (%) | mAP (%) |
| v1 | ✗ | ✗ | ✗ | 10.87 | 12.51 | 10.15 |
| v2 | ✓ | ✗ | ✗ | 21.07 | 23.19 | 18.53 |
| v3 | ✓ | ✓ | ✗ | 25.60 | 28.62 | 20.98 |
| v4 | ✓ | ✗ | ✓ | 24.83 | 27.67 | 20.78 |
| v5 | ✓ | ✓ | ✓ | 33.64 | 36.31 | 28.17 |

Feature visualization:



Top 8 retrieval results:

