

Supplementary Material to: Unsupervised Domain Adaptive Fundus Image Segmentation with Few Labeled Source Data

Qianbi Yu
qiyu2312@uni.sydney.edu.au

Dongnan Liu
dongnan.liu@sydney.edu.au

Chaoyi Zhang
czha5168@uni.sydney.edu.au

Xinwen Zhang
xzha9145@uni.sydney.edu.au

Weidong Cai
tom.cai@sydney.edu.au

School of Computer Science
University of Sydney
Sydney, Australia

Fourier Transform	β parameter		
REFUGE to RIM ONE-r3	0.7963	0.8884	0.6185
RIM ONE-r3 to REFUGE	0.1112	0.3517	0.9209
REFUGE to Drishti-GS	0.4235	0.0720	0.2372
Drishti-GS to REFUGE	0.6194	0.5651	0.0056

Table 1: The selection of the optimal β parameters for Fourier transform. Referring to the searching-based multi-style invariant mechanism (SMSI), the transformation of REFUGE to the other two target domains is required in the first stage as $X_{s \rightarrow t}$, transformation of two target domains to REFUGE is required in the second stage as $X_{t \rightarrow s}$.

© 2022. The copyright of this document resides with its authors.
It may be distributed unchanged freely in print or electronic forms.




Figure 1: Exhibition of synthesis images based on original FDA and SMSI. For original FDA, $\beta = 0.01/0.05/0.09$ values are selected.




Figure 2: Exhibition of synthesis images based on SMSI. Referring to Table 1 for each dataset, three optimal β values are selected.

Methods	Dice Metric [%]			ASD Metric [pixel]		
	Cup	Disc	Average	Cup	Disc	Average
RIM-ONE-r3						
10 shots	78.16	88.45	83.30	9.82	11.78	10.80
20 shots	79.45	88.41	83.93	9.27	10.97	10.12
30 shots	79.68	88.25	83.97	8.99	10.65	9.82
Drishti-GS						
10 shots	83.64	95.47	89.56	11.04	5.25	8.14
20 shots	82.68	96.49	89.59	11.33	4.02	7.68
30 shots	84.93	96.27	90.60	10.06	4.25	7.15

Table 2: Experimental results of our proposed method in terms of Dice and ASD metrics on RIM-ONE-r3 and Drishti-GS target datasets with randomly selected 10, 20, and 30 shots source data.

Methods	Cup Dice	Disc Dice	Average Dice
RIM-ONE-r3			
CADA [1]	64.04	76.64	70.34
TAU [2]	54.20	78.60	66.40
ECSD-Net [3]	80.20	86.50	83.35
BEAL [5]	81.00	89.80	85.40
DPL [10]	79.78	90.13	84.96
pOSAL [6]	78.70	86.50	82.60
Feng et al. [7]	84.10	90.50	87.30
Ours*	83.47	87.85	85.66
Drishti-GS			
CADA [1]	84.00	89.00	86.50
TAU [2]	61.00	88.50	74.75
ECSD-Net [3]	87.60	96.50	92.05
BEAL [5]	86.20	96.10	91.15
DPL [10]	83.53	96.39	89.96
pOSAL [6]	85.80	96.50	91.15
Feng et al. [7]	89.20	96.60	92.90
Ours*	86.68	96.17	91.43

Table 3: Comparing our method to other fundus segmentation methods. the results of other methods are obtained by using 400 fully labeled source domain images, whereas our method only uses 40 source images. The training and testing images in the target domain used by all comparison methods are the same. The results for other methods are directly referenced from the articles. *Our method can achieve comparable and even better UDA segmentation performance only using 10% labeled source data, which indicates the effectiveness of our method, as well as maintaining the data efficiency.

Methods	Dice Metric [%]			ASD Metric [pixel]			Training	Model
	Cup	Disc	Average	Cup	Disc	Average	Time [s/iter]	Size [M]
RIM-ONE-r3								
CyCADA	66.61	76.99	71.80	47.35	41.62	44.48	12.14	31.04
ADVENT	67.99	80.67	74.33	42.04	33.43	37.74	12.19	42.61
PixMatch	70.50	75.20	72.85	16.33	35.90	26.12	13.26	42.61
LTIR	69.28	79.82	74.55	15.52	27.10	21.31	11.04	28.91
MT	70.04	82.66	76.35	13.23	20.54	16.88	8.23	31.04
PCS	65.71	78.00	71.86	18.04	26.09	22.06	14.13	59.34
Ours	83.47	87.85	85.66	7.33	11.33	8.64	79.91	7.62
Drishti-GS								
CyCADA	81.83	91.54	86.68	12.55	12.32	12.43	7.71	31.04
ADVENT	81.82	92.32	87.07	12.43	10.59	15.25	7.33	42.61
PixMatch	75.31	93.13	84.22	16.91	8.34	12.63	8.71	42.61
LTIR	76.72	94.17	85.44	15.82	7.20	11.51	5.94	42.61
MT	75.33	91.62	83.48	16.53	9.79	13.16	8.29	31.04
PCS	78.67	89.63	84.15	17.09	13.64	15.36	8.26	59.34
Ours	86.68	96.17	91.43	8.85	4.35	6.60	86.43	7.62

Table 4: Experimental results of different domain adaptation approaches in terms of Dice and ASD metrics on RIM-ONE-r3 and Drishti-GS target datasets with 40 (10%) labeled source data. Models' training time and models' sizes are also shown.

References

- [1] Cheng Chen, Quande Liu, Yueming Jin, Qi Dou, and Pheng-Ann Heng. Source-free domain adaptive fundus image segmentation with denoised pseudo-labeling. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, 2021.
- [2] Wei Feng, Lin Wang, Lie Ju, Xin Zhao, Xin Wang, Xiaoyu Shi, and Zongyuan Ge. Un-supervised domain adaptive fundus image segmentation with category-level regularization. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, 2022.
- [3] Bingyan Liu, Daru Pan, Zhenbin Shuai, and Hui Song. Ecsd-net: A joint optic disc and cup segmentation and glaucoma classification network based on unsupervised domain adaptation. *Computer Methods and Programs in Biomedicine*, 213:106530, 2022.
- [4] Peng Liu, Charlie T Tran, Bin Kong, and Ruogu Fang. Cada: Multi-scale collaborative adversarial domain adaptation for unsupervised optic disc and cup segmentation. *Neurocomputing*, 469:209–220, 2022.
- [5] Shujun Wang, Lequan Yu, Kang Li, Xin Yang, Chi-Wing Fu, and Pheng-Ann Heng. Boundary and entropy-driven adversarial learning for fundus image segmentation. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 102–110, 2019.
- [6] Shujun Wang, Lequan Yu, Xin Yang, Chi-Wing Fu, and Pheng-Ann Heng. Patch-based output space adversarial learning for joint optic disc and cup segmentation. *IEEE Transactions on Medical Imaging*, 2019.
- [7] Yuhao Zhang, Xiangrui Cai, Ying Zhang, Hong Kang, Xin Ji, and Xiaojie Yuan. Tau: Transferable attention u-net for optic disc and cup segmentation. *Knowledge-Based Systems*, 213:106668, 2021.